MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 30030 (Q,G,P,D)
PRODUCT NAME: CLEAR MAGIC TIRE DRESSING

DATE PREPARED: 03/01/91

SECTION I: MANUFACTURER

TUR GUARD PRODUCTS, INC NE 7TH AVENUR FT LAUDERDALE, FLORIDA 33334-3028

EMERGENCY TELEPHONE NUMBER 305-564-9001 TELEPHONE # FOR INFORMATION 305-564-9001

SECTION II. HAZARDÖÜS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS

OSHA PEL

ACGIH TIV

.17

OTHER

.

Stoddard Solvent

100 ppm

100 ppm

\*This is a compound product and any hazardous components only represent a percentage of the total mixture

SECTION III: PHYSICAL DATA

APPROX BOILING POINT: 346-406 deg F

VAPOR DENSITY: 5.2

EVAPORATION RATE: (N-BUTYL ACETATE - 1)

SVOLATILE: 100

SSOLUBILITY IN WATER: <1%

VAPOR PRESSURE: 1.2

SPECIFIC GRAVITY:

.759 MELTING POINT: N/A

(mm. Hu)

APPEARANCE AND ODOR: Purple color, light odor.

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 125 deg F

FLAMMABLE LIMITS: N/A

LEL: 1.0

UEL: 6.0

XTINGUISHING MEDIA: Use dry chemical, foam or carbon dioxide. Water may be ineffective; however, use water to keep Involved containers cool.

UNUSUAL FIRE & EXPLOSION HAZARDS: Water may be ineffective; however, use water to keep involved containers cool. Water apray may be used to disperse vapors. OSHA/NPFA CLASSIFICATION: II

TIAL FIRE FIGHTING PROCEDURES: Use appropriate MIOSH/MSHA approved respirator. Protect eyes & skin. Vapore are vier than air and may travel to remote ignition sources.

SECTION V: REACTIVITY DATA

STABLE: YES\_x\_ NO\_\_ INCOMPATIBLE MATERIALS: Incompatable with strong acids or bases, oxidizing agents and selected aminus.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield Carbon Monoxide and/or Carbon Dioxide. Do not breath smoke or fumes. Wear appropriate protective equipment.

HAZARDOUS POLYMERIZATION: WILL WILL NOT x OCCUR

POLYMERIZATION CONDITIONS TO AVOID: None

SECTION VI: EMERGENCY AND FIRST AID PROCEDURES

EXEST

Flush with running water for 15 minutes. Get Hedical Aid.

SKIN: Wash with Boap 4 water. Remove 4 discard contaminated clothes 5 shoes
INHALATION: Remove patient to fresh air: Use oxygen if indicated.
INGESTION: DO NOT induce vomiting without medical advice: GET MEDICAL AID AT ONCE.
If vomiting occurs, place patient's head below knees to prevent aspiration.

HEALTH HAZARDS/ROUTES OF ENTRY:
EYE CONTACT: Liquid & high concentrations of vapor will cause eye irritation.

SKIN CONTACT: Prolonged contact may cause drying due to natural oil removal.

INHALATION (DREATHING) 1 May cause nausea, dizzinoss, depression and aneathetic effect above TLV.

INGESTION (SWALLOWING): Nausea, vomiting. Aspiration of liquid may cause preumonitie

CHRONIC DATA: Liver, Kidney, Blood & CNS Diseases may be aggravated.

CARCINGGENICITY: None

NTP: N/A IARC MONOGRAPHS: N/A

OSHA REGULATED: NO

continued...Clear Magic Tire Dressing #30000

SECTION VII: SPILL AND LEAK PROCEDURES

IN CASE OF SPILL OR RELRASE: WARNING: COMBUSTIBLE. Eliminate ALL ignition sources. spills: Evacuate area. Wear appropriate respiratory & protective equipment. Remove leaking containers to open air.
Absorb with clay absorbent & remove outside for safe evaporation. Use only non-sparking tools. VAPOR IS HEAVIER THAN

WASTE DISPOSABLE METHOD: COMPLY WITH ALL LOCAL, STATE & FEDERAL REGULATIONS. All surfactant components are bicodegradable. The solvent is classed "oil". Toxic to aquatic life. DO NOT discharge into streams, ponds or waterways. EPA/HW classified as hazardous waster (Igniteability) 40cFR 261.1 Inclneration or evaporation are the usual disposal methods, with EPA approval. DOT amergency response guidebook DOT 5800.3 \$27. EPA regulation 40 CFR 302 reportable quantity (RQ) not listed.

STORAGE AND SPECIAL PRECAUTIONS: Store in a clean, cool, ventilated area, away form all sources of ignition. Refer to NFPA 30 & OSHA 29cfr 1910.106; "Storage & handling flamm. Liquide, Clean up spills at once. Use only electrically grounded handling equipment. Keep container tightly closed when not in use. Protect containers from damage. Always wear protective equipment. Wash thoroughly after handling. KEEP AWAY FROM CHILDREN. FOR COMMERCIAL & PROFESSIONAL

## SECTION VIII: SPECIAL PROTECTION INFORMATION

VENTILATION:

Provide general ventilation or explosion proof exhaust (6D FTH)

RESPIRATORY PROTECTION: Uso self-contained breathing equipment when TLV is exceeded

PROTECTIVE GLOVES: Recommended

EYE PROTECTION: Use splash goggles or face shield when eye contact may occur, OTHER PROTECTIVE EQUIPMENT: Apron recommended

PRECAUTIONARY WARNING

Workers should not be permitted to handle this product without proper training and using protective equipment. Training before exposure is mandated by 29CFR (OSHA) a State RTK. Avoid prolonged contact with skin, particularly under jewelry (watches & rings) & from contaminated clothing (cuffs & shoes). Containers of this product may be hazardous when "emptied" due to residue & vapors, therefore, all hazard precautions in this data sheet must be observed. Never use a cutting torch on and "emptied" container. Never use air pressure to discharge container contents. Mechanical spraying of this product may increase the hazard potential. Read label directions carefully. Always handle so as to avoid spilling. Clothes & absorbent used to apply or pick up this product retain the same hazards of fire & health as the liquid product. Take care with storage & disposal. Post spill contingency plans in use & storage areas.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: DISCIAIMER OF EXPRESSED AND IMPLIED WARRANTIES:
THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF
HERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OF ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING
THE ACCURACY OF COMPLETENESS OF THIS INFORMATION. THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OF
THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE
FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE HIS OWN DETERMINATION AS TO THE SUITABILITY.

OR THE RECOVER TOR HIS DARRICULAR EMPROSE AND ON THE CONDITION THAT HE RISK OF HIS USE THEREOF. OF THE PRODUCT FOR HIS PARTICULAR PURPOSE AND ON THE CONDITION THAT HE ASSUME THE RISK OF HIS USE THEREOF.

p