

## Safety Data Sheet

Printing date 01/05/2018

Revised On 01/05/2018

## 1 Identification of the substance and manufacturer

**Trade name:** SANDABLE GRAY PRIMER  
**Product code:** 0000201671  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178 USA  
 phone: 815-895-9101  
 www.seymourpaint.com  
**Emergency telephone number:** 1-800-255-3924

Seymour of Sycamore  
 3041 Dougall Avenue, Suite 503  
 Windsor, ONT N9E 1S3 CANADA  
 phone: 800-435-4482  
 www.seymourpaint.com

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

## GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

## Signal word

## Hazard statements

Danger

Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.

## Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

## Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

67-64-1	Acetone	31.84%
74-98-6	propane	15.74%
67-63-0	Isopropyl Alcohol	10.13%
106-97-8	n-butane	9.25%
78-93-3	methyl ethyl ketone	8.64%
13463-67-7	titanium dioxide	5.06%
2807-30-9	Glycol Ether EP	2.79%
557-05-1	zinc stearate	1.43%
64742-47-8	Mineral Spirits	1.24%
108-65-6	PM acetate	1.06%

## 4 First-aid measures

## After inhalation:

Supply fresh air; consult doctor in case of complaints.

## After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

## After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

## After swallowing:

Rinse out mouth and then drink plenty of water.  
 Rinse mouth with water. Do not induce vomiting.

## Most important symptoms and effects:

Dizziness

## Indication of any immediate medical attention needed:

No further relevant information available.

## 5 Fire-fighting measures

## Extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

## Special hazards:

Can form explosive gas-air mixtures.

(Contd. on page 2)

## Safety Data Sheet

Printing date 01/05/2018

Revised On 01/05/2018

Trade name: SANDABLE GRAY PRIMER

(Contd. of page 1)

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.

**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

**7 Handling and storage****Precautions for safe handling  
Storage requirements:**

Use only in well ventilated areas.  
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
	BEI

**74-98-6 propane**

PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX

**67-63-0 Isopropyl Alcohol**

PEL (USA)	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV (USA)	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm
	Long-term value: 492 mg/m <sup>3</sup> , 200 ppm
	BEI

**106-97-8 n-butane**

REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm
	(EX)

**78-93-3 methyl ethyl ketone**

PEL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL (USA)	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm
	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV (USA)	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm
	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
	BEI

**557-05-1 zinc stearate**

PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup>
	*total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup>
	*total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup>

**108-65-6 PM acetate**

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA)	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

**67-63-0 Isopropyl Alcohol**

BEI (USA)	40 mg/L
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Acetone (background, nonspecific)

**78-93-3 methyl ethyl ketone**

BEI (USA)	2 mg/L
	Medium: urine
	Time: end of shift
	Parameter: MEK

**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
Immediately remove all soiled and contaminated clothing.

(Contd. on page 3)

## Safety Data Sheet

Printing date 01/05/2018

Revised On 01/05/2018

Trade name: SANDABLE GRAY PRIMER

(Contd. of page 2)

**Breathing equipment:**

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****Appearance:**

Aerosol.

**Odor:**

Aromatic

**Odor threshold:**

Not determined.

**pH-value:**

Not determined.

**Melting point/Melting range**

Undetermined.

**Boiling point:**

-44 °C (-47.2 °F)

**Flash point:**

-19 °C (-2.2 °F)

**Flammability (solid, gas):**

Extremely flammable.

**Decomposition temperature:**

Not determined.

**Auto igniting:**

Product is not self-igniting.

**Danger of explosion:**

In use, may form flammable/explosive vapour-air mixture.

**Lower Explosion Limit:**

1.7 Vol %

**Upper Explosion Limit:**

12 Vol %

**Vapor pressure:**

Not determined.

**Relative Density:**

Between 0.77 and 0.85 (Water equals 1.00)

**Vapor density**

Not determined.

**Evaporation rate**

Not applicable.

**Partition coefficient: n-octanol/water:**

Not determined.

**Solubility:**

Not determined.

**Viscosity:**

Not determined.

**Water:**

0.0 %

**10 Stability and reactivity****Reactivity:**

Stable at normal temperatures.

**Conditions to avoid:**

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

**Chemical stability:**

Not fully evaluated.

**Possibility of hazardous reactions:**

No dangerous reactions known.

**Incompatible materials:**

No further relevant information available.

**Hazardous decomposition:**

No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****67-63-0 Isopropyl Alcohol**

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

**106-97-8 n-butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**78-93-3 methyl ethyl ketone**

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rbt)

**13463-67-7 titanium dioxide**

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

**108-65-6 PM acetate**

Oral	LD50	8,500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

**Information on toxicological effects:** No data available.**Skin effects:**

No irritant effect.

**Eye effects:**

Irritating effect.

**Sensitization:**

No sensitizing effects known.

**12 Ecological information****Aquatic toxicity:**

Hazardous for water, do not empty into drains.

**Persistence and degradability:**

The product is degradable after prolonged exposure to natural weathering processes.

**Bioaccumulative potential:**

No further relevant information available.

**Mobility in soil:**

No further relevant information available.

(Contd. on page 4)

## Safety Data Sheet

Printing date 01/05/2018

Revised On 01/05/2018

Trade name: SANDABLE GRAY PRIMER

Other adverse effects: No further relevant information available.

(Contd. of page 3)

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

UN-Number UN1950  
 DOT N/A  
 DOT UN1950  
 DOT Consumer Commodity ORM-D  
 Aerosols, flammable  
 1950 Aerosols  
 ADR  
 Transport hazard class(es):  
 Class 2.1  
 Marine pollutant: No  
 Special precautions for user: Warning: Gases  
 EMS Number: F-D,S-U  
 Packaging Group: --  
 UN "Model Regulation": UN1950, Aerosols, 2.1

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

67-63-0 Isopropyl Alcohol  
 78-93-3 methyl ethyl ketone  
 557-05-1 zinc stearate

## Toxic Substances Control Act (TSCA):

All hazardous ingredients for this product are found on the inventory list of substances.

## Consumer Product Safety

## Comission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

## California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide  
 1333-86-4 Carbon black  
 100-41-4 ethyl benzene

## California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

## CANADIAN ENVIRONMENTAL PROTECTION ACT:

## WHMIS Symbols for Canada:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas  
 D2B - Toxic material causing other toxic effects



## EPA:

67-64-1	Acetone	I
78-93-3	methyl ethyl ketone	I
557-05-1	zinc stearate	D, I, II

## 16 Other information

Contact: Regulatory Affairs  
 Date of preparation / last revision 01/05/2018 / -