# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 05/30/2017 Revision date: 05/30/2017 Version: 1.0

# **SECTION 1: Identification**

### Identification

Product form : Mixture : 1K Gun Cleaner Product name : 3680095 / REZ247 Product code

### Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Automotive refinish

# Details of the supplier of the safety data sheet

### Manufacturer

Peter Kwasny GmbH Heilbronner Str. 96 Gundelsheim, 74831 - Germany

T 49(0) 6269-95-20

### Distributor

Peter Kwasny Inc 400 Oser Ave, Suite 1650 Hauppauge, NY 11788

T 1-844-726-6330 (toll free North America)

## **Emergency telephone number**

**Emergency number** : 352-323-3500 (24 hr)

## **SECTION 2: Hazard identification**

## Classification of the substance or mixture

#### **GHS** classification

Flam. Aerosol 1 Press. Gas (Liq.) Eye Irrit. 2A Repr. 2 Simple Asphy

#### 2.2. **Label elements**

# **GHS** labelling

Hazard pictograms (GHS)



GHS04







GHS07

GHS08

Signal word (GHS)

Hazard statements (GHS)

: Danger

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May displace oxygen

Precautionary statements (GHS)

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

# Other hazards

No additional information available

# **Unknown acute toxicity**

Not applicable

05/30/2017 EN (English) Page 1

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

# **SECTION 3: Composition/information on ingredients**

#### 3.1. **Substances**

Not applicable

#### **Mixtures**

Name	Product identifier	%
Dimethyl ether	(CAS-No.) 115-10-6	40.13
Acetone	(CAS-No.) 67-64-1	33.87
n-Butyl acetate	(CAS-No.) 123-86-4	17.96
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	5.99

# **SECTION 4: First aid measures**

### **Description of first aid measures**

First-aid measures after inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.

First-aid measures after eve contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Do not induce vomiting without medical advice. Never give anything by mouth to an First-aid measures after ingestion unconscious person. Get medical advice/attention if you feel unwell.

#### Most important symptoms and effects, both acute and delayed

: May cause irritation to the respiratory tract. Vapours are heavier than air and can cause Symptoms/effects after inhalation suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include

respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.

Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

# **SECTION 5: Firefighting measures**

#### 5.1. **Extinguishing media**

: Water spray. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>). Suitable extinguishing media

: Do not use water iet. Unsuitable extinguishing media

#### Special hazards arising from the substance or mixture 5.2.

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to:

oxides of carbon.

**Explosion hazard** Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries. Vapours may form explosive mixture with air.

Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection may travel considerable distance to an ignition source and flash back to source of vapours.

## **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

General measures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

#### 6.1.1 For non-emergency personnel

No additional information available

# For emergency responders

No additional information available

05/30/2017 EN (English) 2/7

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use

appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential

risk of explosion.

Precautions for safe handling

: Avoid contact with skin, eyes and clothing. Avoid breathing vapours, spray, mist, gas, fume, dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

: Wash contaminated clothing before reuse. Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Hygiene measures

: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Keep out of the reach of children. Store locked up. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Dimethyl ether (115-10-6)			
Not applicable			
Acetone (67-64-1)			
ACGIH	ACGIH TWA (ppm)	250 ppm	
ACGIH	ACGIH STEL (ppm)	500 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
IDLH	US IDLH (ppm)	2500 ppm (10% LEL)	
NIOSH	NIOSH REL (TWA) (mg/m³)	590 mg/m³	
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm	
Xylenes (o-, m-, p- isomers)	(1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm	
ACGIH	ACGIH STEL (ppm)	150 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
n-Butyl acetate (123-86-4)	n-Butyl acetate (123-86-4)		
ACGIH	ACGIH TWA (ppm)	50 ppm	
ACGIH	ACGIH STEL (ppm)	150 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	710 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	150 ppm	
IDLH	US IDLH (ppm)	1700 ppm (10% LEL)	
NIOSH	NIOSH REL (TWA) (mg/m³)	710 mg/m³	
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm	

05/30/2017 EN (English) 3/7

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

n-Butyl acetate (123-86-4)		
NIOSH NIOSH REL (STEL) (mg/m³) 950 mg/m³		
NIOSH	NIOSH REL (STEL) (ppm)	200 ppm

### 8.2. Exposure controls

Physical state

Appropriate engineering controls : Ensure good ventilation of the work station.

: Liquid

Hand protection : Wear suitable gloves.

Eye protection : Wear eye/face protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Avoid release to the environment.

Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance : Aerosol. Colour Clear Odour Characteristic Odour threshold No data available рΗ No data available : No data available Melting point Freezing point : No data available Boiling point : No data available < -18 °C (-0.4 °F) Flash point Relative evaporation rate (butylacetate=1) No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure No data available Relative vapour density at 20 °C No data available Relative density No data available 0.75 a/cm<sup>3</sup> Density Solubility No data available Partition coefficient n-octanol/water : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity, kinematic No data available Viscosity, dynamic No data available Explosive limits : No data available Explosive properties : No data available Oxidising properties : No data available

# 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

05/30/2017 EN (English) 4/7

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

### 10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

ח	imethy	vl ether	(115-10	)-6)
u	mean	vi etilei i		<i>J</i> -U1

LC50 inhalation rat 164000 ppm/4h

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat	50100 mg/m³ (Exposure time: 8 h)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat	29.08 mg/l/4h

n-Butyl acetate (123-86-4)	
LD50 oral rat	10768 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 inhalation rat	390 ppm/4h

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Xylenes	(o-, m-, p-	isomers) (	(1330-20-7)
---------	-------------	------------	-------------

IARC group 3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified.
STOT-repeated exposure : Not classified.
Aspiration hazard : Not classified.

1K	Gun	Cleane	
111	Guii	Cicalic	ı

Vaporizer Aerosol

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause

suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.

Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

05/30/2017 EN (English) 5/7

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Acetone (67-64-1)	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Xylenes (o-, m-, p- isomers) (13	30-20-7)
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
n-Butyl acetate (123-86-4)	
LC50 fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

## 12.2. Persistence and degradability

1K Gun Cleaner	
Persistence and degradability	Not established.

## 12.3. Bioaccumulative potential

1K Gun Cleaner		
Bioaccumulative potential	Not established.	
Dimethyl ether (115-10-6)		
Partition coefficient n-octanol/water	-0.18	
Acetone (67-64-1)		
BCF fish 1	0.69	
Partition coefficient n-octanol/water	-0.24	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
BCF fish 1	0.6 - 15	
Partition coefficient n-octanol/water	2.77 - 3.15	
n-Butyl acetate (123-86-4)		
Partition coefficient n-octanol/water	1.81 (at 23 °C)	

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation. Container under pressure. Do not

drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container.

# **SECTION 14: Transport information**

# Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950
Proper Shipping Name (DOT/TDG) : Aerosols

05/30/2017 EN (English) 6/7

# Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT/TDG)



# **SECTION 15: Regulatory information**

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

## 15.2. International regulations

No additional information available

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# **SECTION 16: Other information**

Revision date : 05/26/2017 Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

05/30/2017 EN (English) 7/7