



ULTRA SMOOTH FINISH

MAXIMUM ADHESION • MAXIMUM PERFORMANCE • EXCELLENT WORKABILITY

POLYESTER PREMIUM FINISHING FINISHING PUTTY

ADVANTAGE #805/#806 Polyester Premium Finishing Putty

Most advanced, maximum performance, polyester finishing and blending putty available. High tech resins deliver maximum adhesion, excellent workability and unbeatable sanding. Easiest sanding putty • Ultra smooth finish • Pinhole free
Maximum adhesion • Stain free and tack free.

COLOR: Aqua (as packaged)

MIX: 2% by weight (50:1 ratio) with supplied cream hardener

SUBSTRATE: Steel. Aluminum. Fiberglass. Body Filler. Wood. 2K Primer. OEM Topcoats. Galvanized and zinc-coated steel. SMC.

SUGGESTED USE: Use for minor body work and surface imperfections such as sand scratches, chips, pinholes and scratches. Ideal for use over body filler.

TOP COAT: Polyester, 2K urethane or 1K primer.

DIRECTIONS Preparation: Clean the surface to remove dirt, oils and wax. Use a 80-180 grit disc to scuff or remove paint. The surface must be dry before application.

Mixing: Puncture the seal under the cap. Place the desired amount of putty on a non-porous mixing board. Knead the cream hardener tub. Add cream hardener at the amount of 2% per weight of filler. For a 4 inch puddle of putty add a ribbon of hardener from edge to edge. Mix filler and hardener completely until a uniform color is produced. Setting time is approximately 3 minutes at 75 degrees F.

Application: Spread a thin coat of mixed putty over the surface using firm pressure to insure adhesion. Thickness should not exceed 1/8 inch. Do not return unused mixed putty to the tube.

Finish: Allow putty to cure for about 20 minutes. Begin sanding with 180-220 grit paper and finish with 320- 400 grit. Follow refinish material suppliers instructions for priming or sealing.

Product Features/Benefits:

Maximum performance and maximum adhesion
Pinhole free - Stain free - tack free
Excellent workability
Unbeatable sanding
Ultra smooth finish

Polyester Premium Finishing Putty Available:

#805 - 16oz. tube

#806 - 30oz. pumptainer



INSTANT MSDS

Scan this QR Code with your
SMART PHONE for instant
MSDS and **TDS** information.



#805/#806

