

5929


Premium Guide Coat

(11oz.)





A must for a perfectly smooth finish. This fast-drying, easy-to-sand formula exposes surface low spots and imperfections. Repair area and contour. Lightly spray with Guide Coat. Begin finish sanding using a sanding block or pad. Low areas will show Guide Coat. Finish sanding until Guide Coat is completely removed and surface is a smooth, dark gray finish. Color: Dark Gray.



- (2) Shake until ball inside breaks loose and rattles. Then hold can at top and swing bottom of can in a circle for 3 minutes making ball travel around bottom groove. Shake up and down occasionally. Repeat shaking procedure for 10 seconds after each minute of use.
- (3) TO SPRAY, hold can 6-8 inches from surface and apply in a sweeping motion with the can held upright. Avoid drips and runs by applying several thin coats at one spraying.
- (4) If spray button becomes clogged, pull off and clean. DO NOT stick pins or wire into can opening. Replace spray button firmly with valve opening pointed away from you.
- (5) To clean valve after use, invert can and spray until only clear gas comes out. Discard empty can in trash pick-up. Do not burn, incinerate, or place in home garbage compactor.

The EZ TOUCH™ FANSPRAY® valve requires 50% less finger pressure than a standard valve. Allows greater coverage with less overspray, and manipulates like a professional spray gun.





Scan this **QR Code** with your **SMART PHONE** for instant **MSDS** and **TDS** information. #5929



Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR XTREME Autobody Products supplier, or visit our website: www.5starxtreme.com - MSDS/TDS/High Resolution photos available ©2014 Part #5929