Detmour

Product Information Sheet



SPRUCE METALLICS AND LACQUERS

A fast drying lacquer spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed with our Spruce primers to ensure proper adhesion.

Suggested Uses:

Metal, wood and wicker Furniture Toys Boats Bikes

Packaging:

Cans per case Shipping weight per case Container Label weight Shipping Classification Hazard Class 12 15 lbs. 16 fluid ounce can 12 ounces (340 grams) Consumer Commodity ORM-D, UN 1950 2.1

Properties:

Coverage Up to 15 square feet Paint or lacquer thinner Cleanup Flammability **Extremely Flammable** Specific Gravity 0.86 Solids Content Glosses: ~12% Flats: ~13% Metallics: ~13% Glosses: 0.86, cannot exceed 0.95 MIR value Clear: 0.77, cannot exceed 0.85 Metallics: 1.16, cannot exceed 1.25 Glosses: ~10% Clear: ~27% Metallics: ~25% HAPs content Storage Temperature 40-100F 50-90F Application Temperature Gasoline Resistance No Heat Resistance 250F Resin System Lacquer Shelf life Guaranteed for 2 years

Dry Time*:

To touch To recoat 5 minutes 20 minutes

*At 7 F, 50% humidity, 1.5 mil thickness

******Curing/Recoat time is extended with multiple coats and excessively thick coats******

Gloss*:

High Gloss, >80 Semi-Gloss, 40-50 Flat, <15 Metallic—Not Applicable

*as measured on a 60 degree gloss meter

Available Colors:				
Part #	Description	UPC Code	Part #	D
98-1	Aluminum	043281002356	98-31	G
98-5	Gold	043281002394	98-32	D
98-6	Brass	043281002301	98-38	S
98-14	Copper	043281002455	98-41	С
98-17	Nickel	043281002486	98-50	G
98-18	Gloss Black Lacquer	043281002493		
98-30	Flat Black Lacquer	043281002561		

t #Description31Gloss Clear Acrylic32Dull Aluminum38Semi-Gloss Black Lacquer41Chrome Aluminum50Gold

Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178

Available Colore

Phone: 815-895-9101 or 800-435-4482 Fax: 815-895-8475 or 800-343-4258 www.seymourpaint.com