



SYSTEM 20 HARDENERS

2K ISOCYANATE HARDENERS

Description	2K Hardener range for U-POL primers, clears and solid colours											
Instructions for use	Use at specified ratios (see specific product data sheets) Use grade for specific conditions. E.g.											
	Temp °C	-5	0	5	10	15	20	25	30	35	40	+45
	Hardener											
	S2031											
	S2030											
	S2032											
	S2033											
VOC Information	System 20 hardeners must not be used on their own, they must always be mixed with a U-POL Clear coat, Primer or solid colour. For mixed Ready for use VOC see individual product data sheets.											
	Grade	S2030	S2031	S2032	S2033	S2034	S2035	S2036				
	VOC g/l As Supplied	603	607	617	618	332	332	333				
	Grade	S2037EV	S2038EV	S2039EV								
	VOC g/l As Supplied	239	232	232								
Health and Safety Statement	FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM . U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.											

U-POL, 1 TOTTERIDGE LANE, WHETSTONE, LONDON, N20 0EY, UK
 Home Sales T: +44(0)870 899 8200; F:+44(0)870 899 8211; E: sales@u-pol.com;
 Export Sales T: +44(0)870 899 8200; F:+44(0)870 899 8299; E: exportsales@u-pol.com;
 Technical T: +44(0)870 899 8310; F:+44(0)870 899 8351; E: technicaldepartment@u-pol.com;
 WEBSITE: WWW.U-POL.COM



HARDENERS

2K ISOCYANATE HARDENERS

Areas of Use	S2030, S2031, S2032, S2032, S2033	S2034, S2035, S2036 S2037EV, S2038EV, S2039EV	
	Primers	Mixed at 3:1, 4:1 or 5:1	Not Applicable
	Clears	Mixed at 2:1, 3:1 or 4:1 and are only suited for non EU compliancy areas	Mixed at 2:1 and 3:1 with EU compliant products
	Solid Colours	Mixed at 2:1 And are only suited for non EU compliancy areas	Mixed at 3:1 and 4:1 with EU compliant products
Shelf Life	9 months shelf life in unopened containers. Lids must be replaced after every use.		

U-POL, 1 TOTTERIDGE LANE, WHETSTONE, LONDON, N20 0EY, UK
Home Sales T: +44(0)870 899 8200; F:+44(0)870 899 8211; E: sales@u-pol.com;
Export Sales T: +44(0)870 899 8200; F:+44(0)870 899 8299; E: exportsales@u-pol.com;
Technical T: +44(0)870 899 8310; F:+44(0)870 899 8351; E: technicaldepartment@u-pol.com;
WEBSITE: WWW.U-POL.COM