



TIGER SEAL

Polyurethane Sealant and Adhesive

Description

TIGER SEAL is a one component urethane sealant and adhesive and is ideal for a number of automotive applications. It will permanently seal and stick body panels and trim. Will seal around windows, doors, lights etc. It will stick to most materials such as steel, aluminum, glass and most plastics.

Health and Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment

Surface preparation and instructions for use

TIGER SEAL PU sealant and adhesive can be used on the following surfaces:-

- Steel, aluminum, brass, iron.
- Fiber Glass and most plastics.
- Glass.
- Wood.
- Ceramics.
- Paint.

Surfaces should be clean and dry and free from grease.

Application

Apply with a standard cartridge caulking gun.

Drying time

30-60 mins. to skin. 0.25"/24 hours to cure through at 72°C and relative humidity of 50%.

Over-painting

TIGER SEAL may be over-painted with most paint systems once fully cured. Can be over-painted once it has skinned if using polyurethane paints.

Product codes

UP0727 - Black 310ml cartridge.
UP0729 - Gray 310ml cartridge.
UP0728 - White 310ml cartridge.

USA U-POL Representative - Sanders and Associates Inc. 1263 Route 31 South, Lebanon, NJ 08833
Tel: (908) 730 8858 or (800) 340 7824 Fax: (908) 730 6621 or (800) 787 5150
E-mail upol@earthlink.net Website : WWW.U-POL.COM