

1 Identification of substance

· **Product details**

· **Trade name:** 40903 1K Clear Aerosol

· **Article number:** 40903

· **Application of the substance / the preparation** Coating

· **Manufacturer/Supplier:**

SEM Products Inc.

651 Michael Wylie Dr.

Charlotte, NC 28217

(704)522-1006

· **Information department:**

labsupport@sem.ws : SEM Products 651 Michael Wylie Dr. Charlotte, NC 28217 : phone 1-704-522-1006, M - TH 7am - 4pm EDT














· **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/Data on components

· **Chemical characterization**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

115-10-6	dimethyl ether Danger:  2.2/1 Warning:  2.5/L	30 - 40%
110-19-0	isobutyl acetate Danger:  2.6/2	13 - 30%
78-93-3	butanone Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	13 - 30%
	ACRYLIC RESIN Warning:  3.2/2, 3.3/2A, 3.8/3	13 - 30%
67-64-1	acetone Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	10 - 13%
108-83-8	2,6-dimethylheptan-4-one Warning:  2.6/3;  3.8/3	1.5 - 5%
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate Warning:  3.2/2, 3.3/2A, 3.8/3	1.5 - 5%
19549-80-5	4,6-dimethylheptan-2-one Warning:  2.6/3;  3.8/3	1-1.5%

3 Hazards identification

· **Hazard description:**



Irritant
Extremely flammable

(Contd. on page 2)

USA

Trade name: 40903 1K Clear Aerosol

(Contd. of page 1)

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

Has a narcotizing effect.

Extremely flammable.

Irritating to eyes and respiratory system.

Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

84.4 % by mass of the contents are flammable

Keep out of the reach of children.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 0

· **GHS label elements**



Danger

2.3/1 - Extremely flammable aerosol.



Warning

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation. May cause drowsiness or dizziness.

· **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

· **Response:**

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

If eye irritation persists: Get medical advice/attention.

· **Storage:**

Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)

Trade name: 40903 1K Clear Aerosol

(Contd. of page 2)

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Trade name: 40903 1K Clear Aerosol

(Contd. of page 3)

Protect from heat and direct sunlight.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEEL 1000 ppm

110-19-0 isobutyl acetate

PEL 700 mg/m³, 150 ppm

REL 700 mg/m³, 150 ppm

TLV 713 mg/m³, 150 ppm

78-93-3 butanone

PEL 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

BEI

67-64-1 acetone

PEL 2400 mg/m³, 1000 ppm

REL 590 mg/m³, 250 ppm

TLV Short-term value: 1782 mg/m³, 750 ppm

Long-term value: 1188 mg/m³, 500 ppm

BEI

108-83-8 2,6-dimethylheptan-4-one

PEL 290 mg/m³, 50 ppm

REL 150 mg/m³, 25 ppm

TLV 145 mg/m³, 25 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Trade name: 40903 1K Clear Aerosol

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	< -18°C (< -0°F)

· **Flash point:** < -18°C (< -0°F)

· **Ignition temperature:** 235°C (455°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.8 Vol %
Upper:	18.6 Vol %

· **Vapor pressure at 20°C (68°F):** 5200 hPa (3900 mm Hg)

· **Density at 20°C (68°F):** 0.786 g/cm³

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents:	84.1 %
VOC content:	71.9 %
	564.9 g/l / 4.71 lb/gl

· **Solids content:** 15.9 %

USA

(Contd. on page 6)

Trade name: 40903 1K Clear Aerosol

(Contd. of page 5)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **DOT regulations:**



- **Hazard class:** 2.1
- **Identification number:** UN1950
- **Packing group:** -
- **Proper shipping name (technical name):** AEROSOLS, flammable

(Contd. on page 7)

Trade name: 40903 1K Clear Aerosol

(Contd. of page 6)

· **Label** 2.1

· **Land transport TDG (Canada) and ADR/RID (Europe):**



· **Hazard class:** 2 - 5F Gases
 · **UN-Number:** 1950
 · **Packaging group:** -
 · **Label:** 2.1
 · **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



· **IMDG Class:** 2.1
 · **UN Number:** 1950
 · **Label** 2.1
 · **Packaging group:** -
 · **EMS Number:** F-D,S-U
 · **Marine pollutant:** No
 · **Propper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 2.1
 · **UN/ID Number:** 1950
 · **Label** 2.1
 · **Packaging group:** -
 · **Propper shipping name:** AEROSOLS, flammable

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

78-93-3	butanone
1330-20-7	xylene
100-41-4	ethylbenzene

(Contd. on page 8)



Trade name: 40903 1K Clear Aerosol

(Contd. of page 7)

· TSCA (Toxic Substances Control Act):	
115-10-6	dimethyl ether
110-19-0	isobutyl acetate
78-93-3	butanone
67-64-1	acetone
108-83-8	2,6-dimethylheptan-4-one
16883-83-3	benzyl 3-isobutyryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
19549-80-5	4,6-dimethylheptan-2-one
25973-55-1	2-(2-HYDROXY-3-5-DI--(TERT)-AMYLPHENYL)BENZOTRIAZOLE
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidiny) sebacate
1330-20-7	xylene
122-99-6	2-Phenoxyethanol
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidiny) sebacate
100-41-4	ethylbenzene
106-79-6	Dimethyl sebacate(Impurity)
104-68-7	Diethylene glycol monophenyl ether

· Proposition 65

· Chemicals known to cause cancer:	
	ACRYLIC RESIN
1330-20-7	xylene
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)		
78-93-3	butanone	I
67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)
None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)		
67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

(Contd. on page 9)



Trade name: 40903 1K Clear Aerosol

(Contd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Irritant
Extremely flammable

· **Risk phrases:**

Extremely flammable.
Irritating to eyes and respiratory system.
Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

Keep in a cool place.
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
Use only in well-ventilated areas.
This material and its container must be disposed of as hazardous waste.

· **Special labeling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
84.4 % by mass of the contents are flammable
Keep out of the reach of children.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement internationale concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)