Page 1/12

Printing date 10/12/2015

Reviewed on 10/12/2015

1 Identification

- · Product identifier
- · Trade name: 781-04 Bright White Basecoat
- · Article number: 781-04
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufactured for: IAMG International Autobody Marketing Group, 1505 North Hayden Road, Ste.111,

Scottsdale, AZ 85257

Information phone : 480.451.4451

- · Information department: 1-87-REFINISH
- · Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1B H360 May damage fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02

GHS07

CHCV

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labeling:

titanium dioxide

4-chloro-alpha, alpha, alpha-trifluorotoluene

benzyl butyl phthalate

acetone

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 2)

· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:

| 13463-67-7 | titanium dioxide | 13 - 30% |
|------------|---|-------------|
| 67-64-1 | acetone | 13 - 30% |
| 1330-20-7 | xylene | 7 - 10% |
| 110-43-0 | heptan-2-one | 7 - 10% |
| 85-68-7 | benzyl butyl phthalate | 1.5 - 5% |
| 41556-26-7 | bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate | <i>≤</i> 1% |
| 108-88-3 | toluene | <i>≤</i> 1% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

BEI

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 5)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 4)

TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm

BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm TLV Long-term value: 233 mg/m³, 50 ppm

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 5)

· Eye protection:



9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

Odor: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55 °C

Flash point: -18 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 465 °C

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 2.6 Vol %

 Upper:
 13.0 Vol %

 ⋅ Vapor pressure at 20 °C:
 233 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.55371 g/cm³
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 56.6 %

(Contd. on page 7)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 6)

VOC content: 19.9 %

713.0 g/l / 5.95 lb/gl

Solids content: 43.4 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Irritant

Carcinogenic categories

· IARC (International Agency for Research on Cancer)

| 13463-67-7 titanium dioxide | 2B |
|--|----|
| 1330-20-7 xylene | 3 |
| 7631-86-9 silicon dioxide, chemically prepared | 3 |
| 85-68-7 benzyl butyl phthalate | 3 |
| 108-88-3 toluene | 3 |

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

USA

(Contd. on page 8)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

UN1993

640D

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

· UN proper shipping name

· DOT

· ADR

· IMDG, IATA

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

Flammable liquids, n.o.s. (Acetone)

FLAMMABLE LIQUID, N.O.S. (ACETONE)

1993 Flammable liquids, n.o.s. (Acetone), special provision

(Contd. on page 9)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 8)

· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA //

· Environmental hazards:

· Marine pollutant: No

Special precautions for user
 Warning: Flammable liquids

· **EMS Number**: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· **Quantity limitations** On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

• **Remarks** ORM-D 49CFR 173-150,156,306

· ADR

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUIDS, N.O.S., SPECIAL

PROVISION 640D (ACETONE), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene 108-88-3 toluene

(Contd. on page 10)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

| | (Contd. of page 9) |
|--|--------------------|
| · TSCA (Toxic Substances Control Act): | |
| 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene | |
| 13463-67-7 titanium dioxide | |
| 67-64-1 acetone | |
| 1330-20-7 xylene | |
| 110-43-0 heptan-2-one | |
| 763-69-9 ethyl 3-ethoxypropionate | |
| 7631-86-9 silicon dioxide, chemically prepared | |
| 85-68-7 benzyl butyl phthalate | |
| 21645-51-2 aluminium hydroxide | |
| 9004-36-8 Cellulose Acetate Butyrate | |
| 41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate | |
| 108-88-3 toluene | |
| 61791-55-7 Amines, N-tallow alkyltrimethylenedi- | |
| 82919-37-7 Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate | |
| 106-79-6 Dimethyl sebacate(Impurity) | |
| · Proposition 65 | |
| · Chemicals known to cause cancer: | |
| 13463-67-7 titanium dioxide | |
| 1330-20-7 xylene | |
| · Chemicals known to cause reproductive toxicity for females: 108-88-3 toluene | |
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| 85-68-7 benzyl butyl phthalate | |
| 108-88-3 toluene | |
| · Cancerogenity categories | |
| · EPA (Environmental Protection Agency) | |
| 67-64-1 acetone | 1 |
| 1330-20-7 xylene | 1 |
| 85-68-7 benzyl butyl phthalate | С |
| 108-88-3 toluene | II. |
| · TLV (Threshold Limit Value established by ACGIH) | |
| 13463-67-7 titanium dioxide | A4 |
| 67-64-1 acetone | A4 |
| 1330-20-7 xylene | A4 |
| 108-88-3 toluene | A4 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| 13463-67-7 titanium dioxide | |
| · GHS label elements | |

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 10)

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling:

titanium dioxide

4-chloro-alpha, alpha, alpha-trifluorotoluene

benzyl butyl phthalate

acetone

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment. P240

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: 1-480-451-4451
- · Date of preparation / last revision 10/12/2015 / 5

(Contd. on page 12)

Printing date 10/12/2015 Reviewed on 10/12/2015

Trade name: 781-04 Bright White Basecoat

(Contd. of page 11)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Lig. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* Data compared to the previous version altered.

USA