Product Name: Rage (Gal) Product identifier: 100106 Revision Date: 12-14-2015 Replaces:



1. Identification

Product Name: Product identifier: Relevant identified uses of the substance or mixture and uses advised against:	Rage (Gal) 100106 Lightweight body filler
Other means of identification Chemical Manufacturer / Importer / Distributor:	ITW Evercoat a division of Illinois Tool Works Inc. 6600 Cornell Road Cincinnati, OH 45242
Emergency telephone number:	513-489-7600 CHEMTREC: 1-800-424-9300 CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;



GHS Classification:	Respiratory Sensitisation Category 1	
	Skin Sensitisation Category 1	
	Reproductive Toxicity Category 1B	
	Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1	
	Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1	
	Skin Corrosion/Irritation Category 2	
	Serious Eye Damage/Eye Irritation Category 2A	
	Germ Cell Mutagenicity Category 2	
	Carcinogenicity Category 2	
	Flammable Liquid Category 3	
	Hazardous to the aquatic environment - Acute Category 3	
GHS Signal Word:	Danger	
GHS Hazard Statements:	Flammable liquid and vapour.	
	Causes skin irritation.	
	May cause an allergic skin reaction.	

Product Name: Rage (Gal) Product identifier: 100106 Revision Date: 12-14-2015 Replaces:

	Causes serious eye irritation.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	Suspected of causing genetic defects.
	Suspected of causing cancer.
	May damage fertility or the unborn child.
	Causes damage to organs.
	Causes damage to organs through prolonged or repeated exposure.
	Harmful to aquatic life.
CUS Procentionary Statements	
GHS Precautionary Statements:	Obtain an acial instructions hafana was
Safety Precautions:	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
	Keep container tightly closed.
	Ground/bond container and receiving equipment.
	Use explosion-proof electrical/ventilating/lighting equipment.
	Use only non-sparking tools.
	Take precautionary measures against static discharge.
	Do not breathe dust/fume/gas/mist/vapours/spray.
	Avoid breathing dust/fume/gas/mist/vapours/spray.
	Wash thoroughly after handling.
	Do not eat, drink or smoke when using this product.
	Contaminated work clothing should not be allowed out of the workplace.
	Avoid release to the environment.
	Wear protective gloves/protective clothing/eye protection/face protection.
	Use personal protective equipment as required.
	In case of inadequate ventilation wear respiratory protection.
First Aid Measures:	IF ON SKIN: Wash with plenty of soap and water.
	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a
	• • • •
	position comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
	if present and easy to do. Continue rinsing.
	IF exposed: Call a POISON CENTER or doctor/physician.
	IF exposed or concerned: Get medical advice/attention.
	Get medical advice/attention if you feel unwell.
	Specific treatment (see on this label).
	If skin irritation occurs: Get medical advice/attention.
	If skin irritation or rash occurs: Get medical advice/attention.
	If eye irritation persists: Get medical advice/attention.
	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
	Take off contaminated clothing and wash before reuse.
	Wash contaminated clothing before reuse.
	In case of fire: Use for extinction.
Storage:	Keep container tightly closed.
	Roop containor righting biosodi

Replaces:	
	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.
Hazards not otherwise classified:	Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Styrene	100-42-5	10 - 30
Titanium dioxide	13463-67-7	0.1 - 1
Acid anhydride	85-43-8	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Eye Contact:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing before reuse.
Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center

Product Name: Rage (Gal) Product identifier: 100106 Revision Date: 12-14-2015 Replaces:

replaces.	
Immediate medical attention and special treatment needed,:	immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. No additional first aid information available
5. Fire-fighting measures	
Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical
Unsuitable extinguishing media: Fire and/or Explosion Hazards:	extinguishing agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical No data available Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons
Special protective equipment and precautions for fire- fighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS No special spill clean-up considerations. Collect and discard in regular trash. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area.

All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage	
Precautions for safe handling:	Mildly irritating material. Avoid unnecessary exposure. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the
Conditions for safe storage:	reach of children. Store in a cool dry place. Isolate from incompatible materials. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact
Materials to Avoid/Chemical Incompatibility::	with incompatible materials. Peroxides Strong acids Strong oxidizing agents Polymerization catalysts

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Styrene	100 ppm	20 ppm	40 ppm STEL; 170 mg/m3 STEL
Appropriate engineering controls.:	No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.		
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of product.		
Skin Protection:	Not normally considered a skin hazard. Where use can result in skin contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of		
Page 5 of 9			

Product Name: Rage (Gal) Product identifier: 100106

Revision Date: 12-14-2015 Replaces:

Respiratory Protection:	neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use
	a NIOSH approved respirator designed to remove particulate
	matter and organic solvent vapors.
Other Protective Equipment:	Splash proof chemical goggles are recommended to protect against the splash of product. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots
General Hygiene Conditions:	All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

9. Physical and chemical properties

Appearance (physical state):	Liquid
Color:	Grey
Odor:	Aromatic
Odor threshold:	No data available
pH:	Neutral
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	145
Flash Point (°C):	38.5
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	6.1
Lower Flammable/Explosive Limit:	1.1
Vapor Pressure:	5 MMHG@20C/68F
Vapor Density:	Heavier than air. Vapors that evolve from this product
	will tend to settle and accumulate near the floor.
Relative Density:	1.2
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	1.36
Auto-ignition Temperature (°C):	490 ° C
Decomposition Temperature::	No data available
Viscosity:	120,000 - 138,000
VOC (as packaged-less exempts and water)	1.48 or 178
VOC (as applied*- 2% by wt hardener- less	0.28 or 34
	Page 6 of 9

Product Name: Rage (Gal)

Product identifier: 100106 Revision Date: 12-14-2015

Replaces:

exempts and water)	
Percent Solids by weight – as packaged	85.00
Percent Solids by weight – as applied* - 2%	97.00
by wt hardener	
VHAP Content by weight – as packaged	17
VHAP Content by weight – as applied* - 2%	3.2
by weight hardener	

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Contamination.
Incompatible materials:	Peroxides Strong acids Strong oxidizing agents Polymerization catalysts
Hazardous decomposition products:	Carbon dioxide Carbon monoxide Styrene oxide Hydrocarbons

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):	Ingestion, Skin contact, Eye contact, Absorption
Immediate (Acute) Health Effects	by Route of Exposure:
Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation,
	headache, chemical bronchitis, asthma-like findings or pulmonary edema.
Skin Contact:	Can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption:	No absorption hazard in normal industrial use. Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include redness, burning, drying and cracking of skin, and skin burns
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.

Product Name: Rage (Gal)

Product identifier: 100106 Revision Date: 12-14-2015 Replaces:

Long-Term (Chronic) Health Effects:

<u>Long</u> Form (on only mount End	
Carcinogenicity:	Suspected of causing cancer. The International Agency for Research on Cancer (IARC) has classified styrene as a group 2B carcinogen (possibly carcinogenic to humans).
Reproductive and	May damage fertility or the unborn child.
Developmental Toxicity:	
Mutagenicity:	Suspected of causing genetic defects.
Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Skin Contact:	Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption:	Upon prolonged or repeated exposure, no hazard in normal industrial use.
Component Toxicology Data	

Chemical Component Oral LD50 Dermal LD50 Inhalation LC50 No data available

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Styrene	Ν	Y	Y
Titanium dioxide	Ν	Y	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):	Toxic to aquatic life.
Persistence and degradability:	No data available
Mobility in soil:	No data available
Other adverse effects (such as	No data available
hazardous to the ozone layer):	

Données sur l'écotoxicité

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues: Safe Handling of Waste:	Spent or discarded material is a hazardous waste. This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261).
Waste treatment methods (including packaging):	Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Product Name: Rage (Gal) Product identifier: 100106 Revision Date: 12-14-2015 Replaces:

 Waste Disposal Code(s):
 D001

 14. Transport information
 UN number:

 UN number:
 UN 3269

 UN proper shipping name:
 POLYESTER RESIN KIT

Transport hazard class(es):3Packing group:III

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information	

Statut TSCA:

A component or components of this product are listed on the TSCA Inventory of Existing Chemical Substances.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	Ν	Ν	Y	N

16.	Other information,	including	date of pre	eparation or last re	vision.

Revision Date:	12-14-2015
Revision Number:	11

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances