Printing date 04/01/2015 Reviewed on 04/01/2015

1 Identification

- · Product identifier
- · Trade name: 61003 Multi-Coat Blank Aerosol
- · Article number: 61003
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-

1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS04

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

acetone

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 1)

P251 Pressurized container: Do not pierce or burn, even after use.
P211 Do not spray on an open flame or other ignition source.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:			
67-64-1	acetone	60 - 70%	
74-98-6	propane	13 - 30%	
78-93-3	butanone	7 - 10%	

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 4)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV refer to Appendix F

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm

Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm

BEI

TLV

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 4)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



· Density at 20 °C:

· Vapor pressure at 20 °C:

Tightly sealed goggles

9 Physical		•	
UPhysical	and c	nomical	nronortios
		1 K 34 I I A K BR V A	

· Information on basic physical and · General Information	chemical properties
· Appearance:	
Form:	Aerosol
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. -44 °C
· Flash point:	-97 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	465 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.7 Vol %
Upper:	13.0 Vol %

8300 hPa

0.72236 g/cm3

(Contd. on page 6)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 5)

Relative density
Vapour density
Evaporation rate
Not determined.
Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents:100.0 %VOC content:35.0 %

623.2 g/l / 5.20 lb/gl

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

67-64-1 acetone

 Oral
 LD50
 5800 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 7)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

UN1950

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

		ormai	

· UN-Number	
· DOT, ADR, IMDG, IATA	

D01, *IIDN*, *IIID0*, *IIII*

· UN proper shipping name · DOT

DOT Aerosols, flammable
ADR 1950 Aerosols
IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 8)

USA ·

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 7) · Transport hazard class(es) $\cdot DOT$ · Class 2.1 · Label 2.1 $\cdot ADR$ · Class 2 5F Gases · Label 2.1 · IMDG, IATA 2.1 · Class · Label 2.1 · Packing group · DOT, ADR, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Gases · EMS Number: F-D,S-U· Transport in bulk according to Annex II of Not applicable. MARPOL73/78 and the IBC Code · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg \cdot ADR Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · IMDG · Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity

(Contd. on page 9)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 8)

· UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3 butanone

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

\cdot EPA	(Environmental	Protection Agend	cv)	ĺ
--------------------	----------------	------------------	-----	---

67-64-1 acetone

78-93-3 butanone

Ι

Ι

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS04

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

(Contd. on page 10)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 61003 Multi-Coat Blank Aerosol

(Contd. of page 9)

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P211 Do not spray on an open flame or other ignition source.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/01/2015 / 3
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* Data compared to the previous version altered.

USA ·