

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 05/29/2017

Revision date: 05/29/2017

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 2K Clear Matte
Product code : 3680065 / REZ531

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Automotive refinish

1.3. Details of the supplier of the safety data sheet

Manufacturer

Peter Kwasny GmbH
Heilbronner Str. 96
Gundelsheim, 74831 - Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc
400 Oser Ave , Suite 1650
Hauppauge, NY 11788
T 1-844-726-6330 (toll free North America)

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24 hr)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Simple Asphy
Flam. Aerosol 1
Press. Gas (Liq.)
Eye Irrit. 2A
Resp. Sens. 1
Skin Sens. 1
Carc. 2
Repr. 2

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust, gas, fume, mist, spray, vapours. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, face protection, protective gloves, protective clothing. In case of inadequate ventilation wear respiratory protection. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|--------------------------------------------------------------------|----------------------|-------|
| Dimethyl ether | (CAS-No.) 115-10-6 | 39.62 |
| Acetone | (CAS-No.) 67-64-1 | 23.78 |
| n-Butyl acetate | (CAS-No.) 123-86-4 | 17.98 |
| Hexamethylene diisocyanate homopolymer | (CAS-No.) 28182-81-2 | 4.82 |
| Solvent naphtha, petroleum, light aromatic | (CAS-No.) 64742-95-6 | 2.97 |
| Ethyl acetate | (CAS-No.) 141-78-6 | 2.70 |
| Xylenes (o-, m-, p- isomers) | (CAS-No.) 1330-20-7 | 1.35 |
| Ethylbenzene | (CAS-No.) 100-41-4 | 0.68 |
| Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester | (CAS-No.) 82919-37-7 | 0.27 |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures after inhalation | : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if condition worsens. |
| First-aid measures after skin contact | : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. |
| First-aid measures after eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention. |
| First-aid measures after ingestion | : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects after inhalation | : May cause respiratory tract irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause stomach distress, nausea or vomiting. |

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|----------------------------------------------|
| Suitable extinguishing media | : Powder, water spray, foam, carbon dioxide. |
| Unsuitable extinguishing media | : Do not use water jet. |

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire hazard | : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Nitrogen oxides. Hydrogen cyanide. Hydrocarbons. |
| Explosion hazard | : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. |
| Reactivity | : No dangerous reactions known under normal conditions of use. |

5.3. Advice for firefighters

| | |
|---------------------------|------------------------------------------------------------------|
| Firefighting instructions | : DO NOT fight fire when fire reaches explosives. Evacuate area. |
|---------------------------|------------------------------------------------------------------|

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Dimethyl ether (115-10-6) | | |
|----------------------------|--------------------------------------|------------------------|
| Not applicable | | |
| Acetone (67-64-1) | | |
| ACGIH | ACGIH TWA (ppm) | 250 ppm |
| ACGIH | ACGIH STEL (ppm) | 500 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| IDLH | US IDLH (ppm) | 2500 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 590 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 250 ppm |
| n-Butyl acetate (123-86-4) | | |
| ACGIH | ACGIH TWA (ppm) | 50 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 710 mg/m ³ |

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| n-Butyl acetate (123-86-4) | | |
|-----------------------------------|---------------------------------------|-----------------------|
| OSHA | OSHA PEL (TWA) (ppm) | 150 ppm |
| IDLH | US IDLH (ppm) | 1700 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 710 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 150 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 950 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 200 ppm |

Hexamethylene diisocyanate homopolymer (28182-81-2)

Not applicable

Solvent naphtha, petroleum, light aromatic (64742-95-6)

Not applicable

Ethyl acetate (141-78-6)

| | | |
|-------|--------------------------------------|------------------------|
| ACGIH | ACGIH TWA (ppm) | 400 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 1400 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 400 ppm |
| IDLH | US IDLH (ppm) | 2000 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1400 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 400 ppm |

Xylenes (o-, m-, p- isomers) (1330-20-7)

| | | |
|-------|-------------------------------------|-----------------------|
| ACGIH | ACGIH TWA (ppm) | 100 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

Ethylbenzene (100-41-4)

| | | |
|-------|---------------------------------------|-----------------------|
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| IDLH | US IDLH (ppm) | 800 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 435 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 545 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 125 ppm |

Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)

Not applicable

8.2. Exposure controls

| | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Hand protection | : Wear chemically resistant protective gloves. |
| Eye protection | : Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Avoid release to the environment. |
| Other information | : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. |

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------------------|-------------------------------------------------------------------------------------|
| Physical state | : Liquid |
| Appearance | : Aerosol |
| Colour | : Clear |
| Odour | : Characteristic |
| Odour threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : < -18 °C (-0.4 °F) |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Vapour pressure | : 340 kPa (2550.2 mm Hg) |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : 0.8 |
| Solubility | : No data available |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : 235 °C (<32 °F) (without propellant) |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : Lower explosive limit (LEL): 1.2 vol % Upper explosive limit (UEL): 18.6 vol % |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

| | |
|-------------|--------|
| VOC content | : 89 % |
|-------------|--------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Nitrogen oxides. Hydrogen cyanide. Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------|-------------------|
| Acute toxicity | : Not classified. |
|----------------|-------------------|

Dimethyl ether (115-10-6)

| | |
|---------------------|---------------|
| LC50 inhalation rat | 164000 ppm/4h |
|---------------------|---------------|

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Acetone (67-64-1) | |
|--------------------------|----------------------------------------------|
| LD50 oral rat | 5800 mg/kg |
| LD50 dermal rabbit | > 15700 mg/kg |
| LC50 inhalation rat | 50100 mg/m ³ (Exposure time: 8 h) |

| n-Butyl acetate (123-86-4) | |
|-----------------------------------|---------------|
| LD50 oral rat | 10768 mg/kg |
| LD50 dermal rabbit | > 17600 mg/kg |
| LC50 inhalation rat | 390 ppm/4h |

| Hexamethylene diisocyanate homopolymer (28182-81-2) | |
|------------------------------------------------------------|----------------------------------------------|
| LC50 inhalation rat | 18500 mg/m ³ (Exposure time: 1 h) |

| Solvent naphtha, petroleum, light aromatic (64742-95-6) | |
|----------------------------------------------------------------|--------------|
| LD50 oral rat | 8400 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | 3400 ppm/4h |

| Ethyl acetate (141-78-6) | |
|---------------------------------|---------------|
| LD50 oral rat | 5620 mg/kg |
| LD50 dermal rabbit | > 18000 mg/kg |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|-------------------------------------------------|---------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | > 4350 mg/kg |
| LC50 inhalation rat | 29.08 mg/l/4h |

| Ethylbenzene (100-41-4) | |
|--------------------------------|--------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat | 17.4 mg/l/4h |

| | |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Skin corrosion/irritation | : Not classified. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified. |
| Carcinogenicity | : Suspected of causing cancer. |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|-------------------------------------------------|----------------------|
| IARC group | 3 - Not classifiable |

| Ethylbenzene (100-41-4) | |
|----------------------------------------------|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |

| | |
|------------------------|--------------------------------------------------------|
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| STOT-single exposure | : Not classified. |
| STOT-repeated exposure | : Not classified. |
| Aspiration hazard | : Not classified. |

| 2K Clear Coat Matte | |
|----------------------------|---------|
| Vaporizer | Aerosol |

| | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects after inhalation | : May cause respiratory tract irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

| Acetone (67-64-1) | |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------|
| LC50 fish 1 | 4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 fish 2 | 6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| n-Butyl acetate (123-86-4) | |
| LC50 fish 1 | 100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC50 fish 2 | 17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| Solvent naphtha, petroleum, light aromatic (64742-95-6) | |
| LC50 fish 1 | 9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Ethyl acetate (141-78-6) | |
| LC50 fish 1 | 220 - 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 fish 2 | 484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| LC50 fish 1 | 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 3.82 mg/l (Exposure time: 48 h - Species: water flea) |
| LC50 fish 2 | 2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 2 | 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris) |
| Ethylbenzene (100-41-4) | |
| LC50 fish 1 | 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 1 | 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 fish 2 | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
| Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1) | |
| LC50 fish 1 | 2.6 mg/l |

12.2. Persistence and degradability

| 2K Clear Coat Matte | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| 2K Clear Coat Matte | |
|-------------------------------------------------|------------------|
| Bioaccumulative potential | Not established. |
| Dimethyl ether (115-10-6) | |
| Partition coefficient n-octanol/water | -0.18 |
| Acetone (67-64-1) | |
| BCF fish 1 | 0.69 |
| Partition coefficient n-octanol/water | -0.24 |
| n-Butyl acetate (123-86-4) | |
| Partition coefficient n-octanol/water | 1.81 (at 23 °C) |
| Ethyl acetate (141-78-6) | |
| BCF fish 1 | 30 |
| Partition coefficient n-octanol/water | 0.6 |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| BCF fish 1 | 0.6 - 15 |

2K Clear Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|------------------------------------------|-------------|
| Partition coefficient n-octanol/water | 2.77 - 3.15 |
| Ethylbenzene (100-41-4) | |
| BCF fish 1 | 15 |
| Partition coefficient n-octanol/water | 3.2 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950

Proper Shipping Name (DOT/TDG) : Aerosols

Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT/TDG) :



SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - WARNING: This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 05/29/2017

Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.