

**U S CHEMICAL & PLASTICS***An Alco Industries Company*

600 Nova Drive SE

Massillon, OH 44646

PH 330-830-6000 - FAX 330-830-6005

**For Chemical Emergency**

CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

(For Canada call collect)

**SECTION I - IDENTIFICATION OF PRODUCT**

**PRODUCT NAME:** RUBBER UNDERCOATING & SOUND DEADENER  
**PRODUCT CODE:** 51030  
**SYNONYM/CROSS REFERENCE:** Undercoating  
**SCHEDULE B NUMBER:** 2715.00.0000

**SECTION II - HAZARDOUS INGREDIENTS**

INGREDIENTS	WGT%	CAS #	TLV/PEL
Aluminum Silicate	5-10%	1332-58-7	TLV 10 mg/m <sup>3</sup> Respirable 2 mg/m <sup>3</sup>
Calcium Carbonate	30-40%	1317-65-3	TLV 10 mg/m <sup>3</sup> Respirable 5 mg/m <sup>3</sup>
Toluene	10-20%	108-88-3	TLV 50 ppm PEL 200 ppm
Petroleum Naphtha	10-20%	64742-89-8	TLV/PEL 300 ppm
Asphalt	10-20%	8052-42-4	TLV 0.5 mg/m <sup>3</sup>
Talc	5-10%	14808-96-6	PEL 2 mg/m <sup>3</sup> Respirable
Propane	5-10%	74-98-6	TLV 2500 ppm PEL 1000 ppm
n-Butane	1-5%	106-97-8	TLV/PEL 800 ppm

**SECTION III - PHYSICAL DATA****APPEARANCE:** Black w/solvent odor**SPECIFIC GRAVITY:** 0.77 – 0.90**VAPOR PRESSURE (mmHG):** N/E**BOILING POINT:** N/E**VAPOR DENSITY:** Heavier than air**EVAPORATION RATE (Ethyl Ether = 1):** Slower than Ethyl Ether**VOLATILES BY WEIGHT:** 43.2%**SOLUBILITY IN WATER:** Insoluble**VOC:** <40% by weight (less Federally Exempt Solvents)

=====

## SECTION IV - FIRE AND EXPLOSION DATA

=====

**FLASH POINT:** -2°F/-19°C Seta Flash Closed cup (Propellant)

**LOWER FLAMMABLE LIMIT %:** N/E

**UPPER FLAMMABLE LIMIT %:** N/E

**FIRE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam

**SPECIAL FIRE FIGHTING PROCEDURES:** Fight like a fuel oil fire. Cool fire exposed containers with water spray. Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARD:** Closed containers exposed to high temperatures, such as fire conditions may explode.

=====

## SECTION V - HEALTH HAZARD/TOXICOLOGICAL PROPERTIES

=====

**OVEREXPOSURE EFFECTS:**

**ACUTE EFFECTS:**

**EYES:** Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

**SKIN:** Contact with skin can cause irritation, (minor itching, burning and/or redness), Dermatitis, defatting may be readily absorbed thru the skin.

**INHALATION:** Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal.

**INGESTION:** Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

**CHRONIC EFFECTS:**

Overexposure to this material has apparently been known to cause the following effects in lab animals: Narcosis, lung, liver, or kidney and central nervous system damage and also reproductive effects.

**CARCINOGEN:** YES \_\_\_\_\_ NO   X  

**TERATOGEN:** YES \_\_\_\_\_ NO   X  

**MUTAGEN:** YES \_\_\_\_\_ NO   X  

Carbon Black has been shown to cause cancer in laboratory animals, but there is insufficient evidence in humans for its carcinogenicity.

**PRIMARY ROUTES OF EXPOSURE:** inhalation, skin

**INHALATION:** If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician if necessary.

**SKIN:** For skin contact, wash promptly with soap and excess water.

**EYES:** For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.

**INGESTION:** If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.

=====

## SECTION VI - REACTIVITY DATA

=====

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Open flames, sparks, heat, electrical and static discharge.

**INCOMPATIBILITY MATERIALS TO AVOID:** Strong acids, alkalis, oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Dioxide, Carbon Monoxide, Carbon and Hydrogen Chloride

**HAZARDOUS POLYMERIZATION:** Will not occur.

---

---

## SECTION VII - SPILL AND DISPOSAL PROCEDURE

---

---

**SPILLS, LEAK OR RELEASE:** Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent.

**WASTE DISPOSAL:** Dispose of in accordance with local, state, and federal regulations.

---

---

## SECTION VIII - PROTECTION INFORMATION

---

---

**RESPIRATORY PROTECTION:** If component TLV limits are exceeded, use NIOSH/MSHA approved respirator to remove vapors. Use an air-supplied respirator if necessary.

**VENTILATION:** Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels.

Explosion-proof ventilation may be necessary.

**PROTECTIVE GLOVES:** To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin

**EYE PROTECTION:** Safety Glasses or goggles with splash guards or side shields.

**OTHER PROTECTIVE EQUIPMENT:** Wear protective clothing as required to prevent skin contact.

---

---

## SECTION IX - HANDLING AND STORAGE PRECAUTIONS

---

---

**STORAGE AND HANDLING:** Use with adequate ventilation. Harmful or fatal if swallowed! Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Do not puncture or incinerate. Contents under pressure.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

---

---

## SECTION X - ADDITIONAL INFORMATION

---

---

**SHIPPING INFORMATION:** Please comply with DOT regulations in USA

HMIS RATING:	Health	1	4 = Extreme
	Fire	4	3 = High
	Reactivity	3	2 = Moderate
			1 = Slight
			0 = Insignificant

Personal Protection - See Section VIII

---

---

**CALIFORNIA PROPOSITION 65:**

This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

**SECTION 313 SUPPLIER NOTIFICATION:**

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CHEMICAL NAME	CAS	% BY WGT
Toluene	108-88-3	10-20%

THIS INFORMATION MUST BE INCLUDED IN ALL MSDS THAT ARE COPIED AND DISTRIBUTED FOR THIS CHEMICAL

=====

ABBREVIATIONS

=====

IARC = International Agency for Research on Cancer  
ACGIH = American Conference of Governmental Industrial Hygienists  
NIOSH = National Institute of Occupational Safety and Health  
TLV = Threshold Limit Value  
PEL = Permissible Emission Level  
DOT = Department of Transportation  
NTP = National Toxicology Program  
N/AV = Not Available  
N/AP = Not Applicable  
N/E = Not Established  
N/D = Not Determined

PREPARED BY: U S CHEMICAL & PLASTICS  
*An Alco Industries Company*  
600 NOVA DRIVE SE  
MASSILLON, OH 44646

TELEPHONE NBR 330-830-6000  
FAX NBR 330-830-6005

DATE REVIEWED: May 5, 2007  
DATE REVISED: May 5, 2007  
REVISION: Section: III

The information in the Material Safety Data Sheet has been compiled from our experience and from data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the MSDS is the latest one issued.