

3M™ Perfect-It™ 3000 Trizact™ Polish
PN 06070 Quart ID 60-9801-0915-5

- Effectively removes 3M™ Trizact™ Hookit™ II Foam Disc grade P3000 sand scratches
- Ideal for spot/small panel repairs
- Quickly and effectively removes compounding swirl marks
- Good handling - easy cleanup - high gloss finish

WARNING! COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL. MAY CAUSE EYE AND DELAYED SKIN IRRITATION.
Read carefully other cautions on the side/back panel.

3M™ Perfect-It™ 3000 Trizact™ Polish is designed to remove grade P3000 3M™ Trizact™ Hookit™ II Abrasive Disc sand scratches, or to remove compounding swirl marks, and leave an excellent high gloss finish.

Directions for Use: Polish using an air or electric buffer (1000-2500 rpm) equipped with a 3M™ Perfect-It™ Foam Polishing Pad.

1. Shake container well before using.
2. Apply enough polish to the paint surface to work a spot repair, or a two foot by two foot area.
For best results, use enough polish to work a spot repair for about 30 seconds, or a two foot by two foot area for about one to two minutes.
- 3a. Buff spot repairs using medium pressure to effectively remove grade P3000 sand scratches.
- 3b. Buff large areas using light to medium pressure.
4. Reduce pressure as polish begins to dry and buff to a high gloss. Use a 3M™ Perfect-It™ III Detailing Cloth to remove any remaining residue.

Note: If glaze slings onto an adjacent panel, remove spatter using a 3M™ Perfect-It™ III Detailing Cloth before glazing the next panel.

PROTECT FROM FREEZING

WARNING! Combustible liquid and vapor. May cause eye, delayed skin, nose and throat irritation and may affect the brain or nervous system causing dizziness, headache or nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Contains: Water (7732-18-5); Aluminum Oxide (1344-28-1); Acid Treated Light Petroleum Distillates (64742-14-9); Decamethylcyclopentasiloxane (541-02-6); Aluminum Silicate Clay (66402-68-4); Dodecamethylcyclohexasiloxane (540-97-6).

Precautions: Keep away from heat and flame. Use only with adequate ventilation. Avoid eye and skin contact. Avoid breathing vapors. Do not ingest. Close container after each use. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

Suggested First Aid: Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. **Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention. **Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention. **If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

Warranty and Limited Remedy: This product will be free from defects in material and workmanship at the time of shipment. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If this product is defective, your exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: 3M and seller will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

Additional Product Safety and Health Information Source:

Material Safety Data sheet (MSDS 19-0029-9) or

3M Automotive Aftermarket Division

3M Center/Bldg. 223-6N-01

St. Paul, MN 55144-1000

1-877-666-2277 (1-877-MMM-CARS) or 651-737-6501

www.3M.com/automotive

3M, Perfect-It, Trizact and Hookit are trademarks of 3M Company.

© 3M 2004