




# **Hose Fittings**

# **Designed to Optimize Air** Flow for Top Spray Gun and Air Tool Performance



## PRESSURE DROP COMPARISON AT 50 PSI INLET AT 25 SCFM



The chart above shows test data at 25 SCFM using:

DeVilbiss high flow HC-4720 coupler, HC-4419 stem. RBL 611 coupler, 612 stem. Sharpe 8320 coupler, 8330 stem. Original DeVilbiss P-HC-4120 coupler, P-HC-201 stem. Milton/Sata " P" style 1804 coupler, 1810 stem. Milton " M" style S715 coupler, S727 stem. Sata/Milton "T" style 784 coupler, 786 stem. Milton " A" style S775 coupler, S777 stem.

#### **Reusable Connections**

**Hose Size and Type** 

Size I.D.	Size O.D.	Fits DeVilbiss Hose No.	(M) Male (F) Female Connection Thread Size	Straight Connections Female Complete Connection No.
1/4"	1/2"	H-1957 H-1975-1	1/4" NPS (F) 3/8" NPS (F)	P-HC-4523 P-HC-4543
5/16"	5/8"	H-1921	1/4" NPS (F) 1/4" NPS (M)	P-HC-4527 P-HC-4599
3/8"	11/16"	H-1973-1	1/4" NPS (F) 3/8" NPS (F) 1/4" NPT (M)	P-HC-4528 P-HC-4548 P-HC-4955

#### **Quick Disconnects - High Flow Ball and Ring Lock Type**

(For use with HVLP Spray Equipment)

Connection Number	Order Number	Thread Size	W
HC-4719 (A)	240147	1/4" NPT (M)	ſ
HC-4720 (B)	240148	1/4" NPT (F)	
Stem Number			
HC-1166 (C)	240015	1/4" NPT (M)	
HC-4419* (D)	240145	1/4" NPS (F)	
*Designed for s	enray dune	Special cone seat prevents leaks!	









#### Nipples (MBE) Male Both Ends

Part	Straight Type	
Number	Male Thread	Male Thread
AD-31	1/4" NPS	1/4" NPS
H-2008	1/4" NPS	1/4" NPT
H-1446	3/8" NPS	3/8" NPS
AD-11	3/8" NPS	3/8" NPT

### **Adapters**

Part	Straight Type		
Number	Male Thread	Female Thread	
AD-404	1/4" NPS	3/8" NPS	
P-H-4105	3/8" NPS	1/4" NPS	

#### Valves - Ball Type

Part Number	Thread	
VA-540	3/8" NPS (M) x 3/8" NPT (M)	
VA-542	1/4" NPS (M) x 1/4" NPT (M)	
VA-595	1/2" NPT (M) x 1/2" NPT (M)	

#### Coupler

Part Number	Thread	
SSP-69	1/4" y 1/4" NPT (F)	