



7772() XXX ADHESION PROMOTER

TECHNICAL DATA SHEET

Description

7772() XXX ADHESION PROMOTER promotes adhesion of topcoat materials when repairing or refinishing interior and exterior automotive surfaces. **7772()** may be used on a variety of materials including flexible and rigid problem plastics, TPO, PP, SMC, aluminum, steel, glass, chrome and most painted surfaces.

Features

- Improves adhesion of topcoat materials to various substrates
- Easy to apply
- Available in aerosol or RTS gallons

Typical Properties

Containers

77721 – gallon and **77723** - aerosol

Color

Clear

VOC **77721**

6.36 #/g1 (762.0 g/l)

VOC **77723**

4.94 #/g1 (591.4 g/l)

Handling and Application

PREPARATION:



Clean area with **39362 SEM SOAP** or **3833() SCUFF & CLEAN** and a gray scuff pad. Rinse with water and allow to dry. Next, thoroughly clean plastic surfaces with **3835() PLASTIC/LEATHER PREP** and non-plastic surfaces with **3837() SEM SOLVE**. Use a clean, lint free towel and wipe in one direction. Sand area to be refinished with 400 grit sandpaper. Blow off dust and clean again with **3835()** or **3837()**.

APPLICATION:



Apply one light coat. Allow 5 minutes flash time followed by one full wet coat. Allow to flash 15 minutes but no longer than 30 minutes before top coating.



Refinish with **SEM COLOR COAT**, **SEM BUMPER COATER**, all base coat/clear coat systems, urethanes, acrylic enamels, alkyd enamels and acrylic lacquers.

NOTE: Adhesion improves with time. Do not rush to reinstall part.

CLEAN UP:



Clean spray equipment with quality grade acrylic lacquer thinner.

STORAGE:



7772() XXX ADHESION PROMOTER should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **77723** is 2 years when stored under normal conditions, while the shelf life for **77721** is 5 years.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
651 Michael Wylie Drive Charlotte, NC 28217
Tel: 800/ 831-1122
Fax: 704/ 522-7008
www.sem.ws