FM-71

FINELINE MASKING TAPE

INTERTAPE POLYMER GROUP

TECHNICAL DATA SHEET

DESCRIPTION

FM-71 "fine line" masking tape uses thermally stabilized PVC backing with a rubber-based pressure-sensitive adhesive. This tape is designed to offer a high degree of conformability without excessive stretch. FM-71 will hold and cleanly remove from surfaces in the presence of 250° F (120° C) temperatures for at least 30 minutes. FM-71 assures the user of a secure lay-down, no residue on de-mask and a sharp / clean separation line.

PRODUCT APPLICATIONS

Preferred for medium to high temperature applications where a sharp, fine line is required. FM-71 is used where a tape must meet a variety of paint masking applications.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing Blue P.V.C.

Adhesive Natural Rubber

Tensile Strength (lbs/in of width) 14 lbs/in (61.3 N/25mm)

Adhesion to Steel (oz/in of width) 20 oz/in (5.5 N/25mm)

Elongation (% at break) 150%

Total Thickness (mils) 5.4 mil (0.137 mm)



3647 Cortez Road West | Bradenton, FL 34210 | USA Customer Service: 800.IPG.8273 | 800.474.8273 Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.



EFFECTIVE: 02/11