

# PRODUCT FEATURES & APPLICATION



## Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

### **SUPER ACID ETCH AND PRIMER AEROSOL**

Stock SEPA

Part # 24010

*Description SUPER ACID ETCH AND PRIMER* is a ready to use aerosol etch primer. It is used for priming bare metal surfaces this promotes adhesion of paint and prevents steel from rusting.

*SUPER ACID ETCH AND PRIMER* is chromate free. Typical applications are over rubbed through areas prior to painting, on new bare metal panels or over bare seams before sealant is applied.

#### **Features:**

##### *Preparation and Instructions:*

##### **SUPER ACID ETCH AND PRIMER**

may be applied to the following surfaces;-

- Bare steel.
- Aluminum.
- Galvanized and Zinc coated steels.
- Fully cured paint.
- Polyester body fillers and fiber glass.

#### **Application Instructions:**

##### *Application:*

Thoroughly clean and degrease surfaces with Dominion Sure Seal's "SURE WIPE"  
Abrade wet or dry with 280 –320 grit abrasive.  
Re-clean, dry and degrease

1. Shake aerosol thoroughly before use for a minimum of 2 minutes.
2. Keep the can 12 ins. from the panel, spray light even coats
3. Apply 1-2 coats.
4. Allow 3-5 minutes flash off time between coats.
5. Allow 10-20 minutes before overcoating.
6. Drying time is dependent upon film thickness, humidity and temperature.

**Over-painting** Under normal circumstances it is not necessary to flat **SUPER ACID ETCH AND PRIMER** and should be directly overcoated.

**SUPER ACID ETCH AND PRIMER** may be over coated directly with top coat.

However if the repair requires additional build, a primer filler should be used before top coat is applied.