



# Montana® Big Sky® Product Information Sheet

Technical Support (800) 328-4892

TDS\_BS\_AP300

## AP300™ Blue Shield™ Liquid Spray Mask

### COMPONENTS (REQUIRED)

AP300™ Liquid Spray Mask

### DESCRIPTION:

AP300™ Blue Shield™ Liquid Spray Mask is designed to replace plastic sheeting or car covers and provides start to finish protection. This water based ready-to-spray liquid mask is fast and easy to apply and dries to a tack-free film that can be taped and re-taped during border masking with paper. AP300™ can be baked multiple times at temperatures up to 170°F / 76°C. One even coat protects any part of the vehicle including grills, wheel wells, engine compartments, and vinyl tops.

### MIX BY VOLUME

- N/A - Product is ready-to-spray
- OPTIONAL: AP300™ may be reduced an additional 5% to 10% with clean water if needed.

### APPLICATION

- Montana Big Sky® AP300™ Liquid Spray Mask may be applied using conventional, HVLP, or airless spray equipment.
- Suggested Fluid tips range from 1.6mm to 1.8mm.
- Border mask around the area to be painted with 18" paper.
- Fold masking paper back over repair area.
- Apply one-single wet coat of AP300™ Liquid Spray Mask to the surfaces to be protected. This includes windows, wheels and tires, door jams, and cured painted surfaces.  
**Tip:** Apply only enough material to maintain a complete protective film. Excessive film build will require longer rinsing to remove from the surface.
- Allow AP300™ to dry. Fold paper over onto the surface and tape. To minimize or eliminate additional taping, fold the paper over in the wet spray mask.
- Finish repair area.
- AP300™ Liquid Spray Mask is easily removed with water and a wash mitt during the wash and detail period.

### CLEAN-UP

Clean spray equipment immediately following application with water, followed by a quality thinner or spray gun cleaner.

### DISPOSAL

Dispose of all paint and paint related materials in accordance with state and local regulations.

### SAFETY & HEALTH

Read and follow all technical product information, labels, and SDS prior to application. Keep product out of reach of children and animals. Always wear proper safety equipment (respirator, gloves, eye, and clothing protection) when using this product.

### COMPANY INFORMATION

ChemSpec USA, LLC.  
9287 Smucker Road  
Orrville, Ohio 44667  
Toll Free: (800) 328-4892  
Fax: (330) 669-3965  
Website: [www.chemspecpaint.com](http://www.chemspecpaint.com)