

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Positive-drive orbital polisher

XC 3401 VRG

Order number 322.008



Technical attributes

Max. polishing pad diameter	160 mm
Velcro backing pad Ø	140 mm
No load speed	160-480 rpm
Orbit	8 mm
Orbit rate, no load	3200-9600 opm
Power input	1010 watt
Power output	590 watt
Cable length	4,0 m
Weight	2,6 kg

Positive-drive orbital polisher

- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + 8 mm orbit for high efficiency
- + Permanent direct drive for an even polished surface
- + Cushioned special hook and loop pad for polishing.
- + Removable, ergonomic handle and guard for optimum handling in all applications
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints
- + Counterweight for smoother operation
- + Low height and low weight
- + Spindle lock
- + This machine is also available in 110 V

Standard equipment

1 bail handle	333.565
1 special velcro backing pad, 140 Ø	342.637