

# LEATHER

## 1 CLEAN


Clean with **SEM Soap** and a gray scuff pad. Scrub thoroughly, paying close attention to textured or recessed areas. Rinse with water and dry or wipe off with a damp cloth.



**SEM Soap**  
Part: 39362  
15 oz. Tube

## 2 PREP

Clean with **Plastic & Leather Prep** using a lint free towel and wiping in one direction. If contamination still exists after cleaning, water will bead on the surface. Repeat steps 1 and 2 until beading no longer occurs.



**Plastic & Leather Prep**  
Part: 38351  
Gallon  
Part: 38353  
16 oz. Aerosol  
Part: 38354  
Quart

## 3 SCUFF

Scuff the leather with a clean gray scuff pad or 400-600 grit sandpaper. Blow off dust and clean again with **Plastic & Leather Prep**.

## 4 APPLICATION

Apply light coats of **Classic Coat**, allowing 5-10 minutes between coats, until hiding or desired uniform color is achieved.

**NOTE:** Even though film can appear dry to touch, the substrate should not be subjected to heavy abuse or abrasion for 24 hours.



**Classic Coat™**  
16 oz. Aerosols

# VINYL

## 1 CLEAN

Clean with **SEM Soap** and a gray scuff pad. For vinyl convertible tops, use a nylon bristle brush. Scrub thoroughly, paying close attention to textured or recessed areas. Rinse with water and dry or wipe off with a damp cloth.



**SEM Soap**  
Part: 39362  
15 oz. Tube

## 2 PREP

Clean with **Vinyl Prep** using a damp lint free towel wiping in one direction. Or, apply **Zero VOC Surface Cleaner** directly to the surface or wipe on with a clean cloth. Wipe surface with enough material to adequately float contaminants out of sand scratches.

Wipe dry in one direction with a clean, lint-free cloth, turning and changing cloths often. If contamination still exists, water will bead on the surface. Repeat steps 1 and 2 until no beading occurs.

**CAUTION:** Do not allow **Vinyl Prep** or **Zero VOC Surface Cleaner** to splash or stand on painted surface as discoloring may occur.



**Vinyl Prep**  
Part: 38343  
16 oz. Aerosol  
Part: 38344  
Quart



**Zero VOC Surface Cleaner**  
Part: 40401  
Gallon  
Part: 40404  
Quart

## 3 APPLICATION

Apply light coats of **Classic Coat**, allowing 5-10 minutes between coats, until hiding or desired uniform color is achieved.

**NOTE:** Even though film can appear dry to touch, the substrate should not be subjected to heavy abuse or abrasion for 24 hours.



**Classic Coat™**  
16 oz. Aerosols



The Right Choice