



# PREMIUM POWDER GUIDE COAT

## TECHNICAL DATA SHEET



Check local VOC regulations to ensure compliance of all products in your area.

### DESCRIPTION

Dry powder for identifying low spots, pinholes and other surface defects when sanding primer.

### FEATURES

- Dries instantly
- Sandable immediately
- Will not clog sandpaper
- Improves repair quality
- Eliminates messy applicators

### SUITABLE SUBSTRATES

- Any 1K or 2K primer

### TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
38253	Premium Powder Guide Coat	Black	16 oz. Aerosol

MIR (Aerosol): Category ABP < 1.55

### HANDLING AND APPLICATION

#### PREPARATION:

Complete repair and allow primer to dry according to manufacturer's instructions.

#### MIXING:

Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).

#### APPLICATION:

Apply a light "mist" coat over the area. Sand until **Premium Powder Guide Coat** can no longer be seen. Wipe off any overspray with a dry cloth.

#### Note:

If clogging develops, remove spray button with a twisting motion and clean with **XXX Gun Cleaner** or material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

After each use, turn can upside down and spray several seconds to clear spray tip.



Check local VOC regulations to ensure compliance of all products in your area.

---

## **STORAGE:**

**Premium Powder Guide Coat** should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Premium Powder Guide Coat** is 3 years when stored under normal conditions.

### **Technical Consultation Service**

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

### **Disclaimer:**

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.